



2




**Kovse, galvaniserede**

Målene nedenfor er vejledende, og der kan være mindre afvigelser.

**Thimbles, galvanized**

The dimensions mentioned below are just instructive and departures may occur.



DIN 6899


\*Elektro galvaniseret /  
Electro galvanised

Varenr. / Item no.	Wire dia. mm	C mm	l mm	S mm	RW mm
261-500-1025	2	12	19	1,1	3
261-500-1035	3	13	21	1,1	4
261-500-1040	4	14	23	1,6	5
261-500-1050	5	16	25	1,7	6
261-500-1060	6-7	20	32	2	8
261-500-1070	8-9	24	38	3,5	10
261-500-1100	10-11	28	45	3,5	12
261-500-1120	12-13	32	51	3,5	14
261-500-1140	14-15	36	58	4	16
261-500-1160	16-17	40	64	6	18
261-500-1180	18-19	45	72	6	20
261-500-1200	20-21	50	80	6	22
261-500-1220	22-23	56	90	8	24
261-500-1240	24-25	62	99	6,5	26
261-500-1260	26-27	70	112	8	28
261-500-1280	28-29	75	120	8	30
261-500-1300	30-31	80	128	8	32
261-500-1320	32-33	95	152	9	34
261-500-1340	34-35	100	160	9	36
261-500-1360	36-37	110	176	9	38



**Kovse rustfrie,  
polerede**

**Thimbles stainless,  
polished**



Varenr. / Item no.	Dim. mm	A mm	B mm	E mm	Vægt / Weight kg/stk./pcs.
280-450-1030	3,0	12,0	19,0	3,0	0,0020
280-450-1040	4,0	13,0	21,0	4,0	0,0040
280-450-1050	5,0	14,0	23,0	5,0	0,0050
280-450-1060	6,0	16,0	25,0	6,0	0,0070
280-450-1070	7,0	18,0	28,0	7,0	0,0120
280-450-1080	8,0	20,0	32,0	8,0	0,0150
280-450-1100	10,0	24,0	38,0	10,0	0,0290
280-450-1120	12,0	28,0	45,0	12,0	0,0520
280-450-1140	14,0	32,0	51,0	14,0	0,0520
280-450-1160	16	38,0	61,0	17,0	0,1900
280-450-1180	18	40,0	64,0	18,0	0,2030
280-450-1200	20	45,0	72,0	20,0	0,2730