

pewag MWP Enlarged master link

What counts, is the inner width.

This master link corresponds to EN 1677-4 with a load capacity according to G12. It is used to create I- and II-leg chain slings using the Connex CWP connecting link and opens up universal connection possibilities thanks to the flattened section incorporated in its design. It may also be used as an end link in single- or multiple-leg chain slings.

With its extra-large inner width compared to the AWP master link, it is also suitable for larger single hooks according to DIN 15401. Refer to the table for the correct chain dimensions and single hook size.

This enlarged master link is manufactured according to EN 1677-4 with the mechanical values of G12 and comes with BG-approval. The surface of the master link has a light blue powder coating.



MWP Enlarged master link	Code	Load capacity [kg]	Can be used up to single hook according to DIN 15401 no.	d [mm]	t [mm]	w [mm]	s [mm]	Weight [kg/pc.]	For 1-leg slings	For 2-leg slings
	MWP 13	2,360	4	14	120	70	10	0.46	7	-
	MWP 16	3,200	5	17	140	80	13	0.74	8	-
	MWP 18	5,000	6	19	160	95	14	1.05	10	-
	MWP 26	10,100	10	27	190	110	20	2.47	13	-
	MWP 36	17,500	10	38	275	150	29	7.48	-	16